

Specification



Model	JIVA HS-2308	JIVA HS-2310
Processor	Intel Pineview dual core D525 CPU, 1.8GHz, 1M Cache	
System Memory	DDR3 800MHz, SO-DIMM x 1, max. 4GB; factory default 1GB	DDR3 800MHz, SO-DIMM x 1, max. 4GB; factory default 2GB
Storage Device	2.5" SATA HDD and/or SSD; factory default 16GB SSD x 1	2.5" SATA HDD and/or SSD; factory default 320GB HDD x 1
Display	8" 800 x 600 LCD panel	9.7" 1024 x 768 LCD panel
Touch	5-wire resistive touch panel	5-wire resistive touch panel (Bezel-free)
Built-in Printer	3" thermal printer with auto cutter, 200mm/sec print speed	
Power Supply	12V DC power adaptor, 120W	
OS Support	Windows 7 / POSReady 7 / Windows XP Pro / POSReady 2009 / Linux	
Connectivity		
LAN Port	10 / 100 / 1000Mb x 1	
Serial Port	DB9 x 2 + RJ45 x 1 with 5V/12V support on COM1 / COM2 / COM3, RJ-45 to DB9 cable optional	
Parallel Port	Yes	
Standard USB Port	5	
Audio Port	Line out	
PS/2 Port	Yes	
VGA Port	D-SUB, 15 pins, with 12V support for Posiflex monitor	
Mini-PCIe slot	Yes, for half size card	
CR Port	1, control 2 CR	1, control 2 CR
Physical Dimension		
Dimension (W x D x H in mm)	205 x 185 x 362	224.5 x 185 x 387
Weight (N.W. in Kg)	4.1	4.2
Environment		
Operation Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)	
Storage Condition	(-20°C) - 70°C, 10%RH - 90%RH	
Options		
SSD	16GB minimum	
MSR	Integrated 3 track module	
Smartcard Reader	Integrated	
RFID	Integrated, support MIFARE ultralight and classic 1K card	
Finger Print Sensor	Integrated	
LM-6507	7" 800 x 480 rear-mount 2nd display for JIVA HS Series (USB interface)	
PD-6507	7" color graphical line display, rear-mount (USB interface)	
PD-2607UE	2 x 20 VFD, rear-mount, USB with Virtual COM support	
PD-340UE	2 x 20 LCD, rear-mount, USB with Virtual COM support	
WIFI	Internal mini-PCIe WIFI module with PIFA antenna	
Certifications		

JIVA HS Series

Taking Space Saving To Extreme



Design and Manufacturing In Taiwan by Posiflex Technology Inc.
The product information and specifications are subject to change without prior notice.

2013Q3C1



Posiflex Technology Inc. (Headquarters)
TEL +886-2-2299-1599 **FAX** +886-2-2299-1819
MAIL sales@posiflex.com.tw **WEB** www.posiflex.com
 No. 6, Wuquan Rd., Wugu Dist., New Taipei City 24886, Taiwan

Authorized Distributor / Reseller

SINCE 1984

www.posiflex.com