

# Hisense

10 INCH RUGGED TABLET POS SYSTEM WITH OPTIONAL SMART DOCK



**Hisense**  
Integrated  
Card Reader  
as Standard

## Hisense HM618

10.1" Rugged Tablet  
High Performance POS Terminal



• Sleek design that suites any restaurant environment.



• Sleek design that suites any restaurant environment.

### Key Features

- 10.1" Wide Screen.
- Bezel-Free, PCT Multi-Touch Screen.
- Standard Integrated Card Reader.
- Meets IP54 Standards.
- Sturdy Hand Strap Standard.

### Options

- NFC Module.
- 1D Scanner Honeywell.
- 2D Scanner Honeywell.
- 4G Module.





# Hisense

## HM618 10.1" Rugged Tablet

### High Performance POS Terminal

#### Key Features

- 10.1" Wide Screen.
- Bezel-Free, PCT Multi-Touch Screen.
- Standard Integrated Card Reader.
- Meets IP54 Standards.
- Sturdy Hand Strap Standard.

#### Options

- NFC Module.
- 1D Scanner Honeywell.
- 2D Scanner Honeywell.
- 4G Module.



**Note:** Tablets do not communicate with Charging Dock or Smart Dock when removed.



- The multi-touch screen meets IP54 standards for dust & liquid.



- The HM618 has an integrated card reader as standard.



- The HM618 has a sturdy hand strap as standard.



#### HISENSE HM618 SPECIFICATION

<b>Processor:</b>	Intel Cherry Trail Z8350.
<b>O/S:</b>	Windows 10 IoT Enterprise LTSB.
<b>Display:</b>	10.1" TFT LCD (LED Back-Light).
<b>Resolution:</b>	1280 x 800.
<b>Brightness:</b>	Adjustable Up to 350 cd/m2.
<b>Touch Panel:</b>	True-Flat Projected Capacitive.
<b>Memory:</b>	4GB RAM.
<b>Storage:</b>	64GB eMMC.
<b>Camera:</b>	Front: 2 Megapixel. Back: 5 Megapixel.
<b>Wireless:</b>	Wi-Fi: Dual Band WiFi (2.4G / 5G). Bluetooth: Integrated Bluetooth V4.1.
<b>Speaker:</b>	Two Internal Speakers.
<b>Audio:</b>	3.5mm Socket.
<b>MCR:</b>	Standard Integrated TripleTrack Card Reader.
<b>Battery:</b>	Type: 3.7V 9000mAh. Life: 8 Hours with 50% Brightness.

<b>Tablet Dock Connection:</b>	10 Pin Pogo Style Connector.
<b>Tablet I/O Interface:</b>	Audio Jack / Nano SIM / Micro SD / Micro USB / USB V3.0 / DC Jack / Micro HDMI.
<b>Charging Dock I/O:</b>	5V Charging / Two USB V2.0.
<b>Smart Dock I/O:</b>	Cash Drawer / 24V Power / Two RS232C / Ethernet / Three USB V2.0.
<b>Power Supply:</b>	Tablet/Charging Dock: 5V/4A External Power Adaptor 100-240V 50/60Hz. Smart Dock: 24V/3.75A External Power Adaptor 100-240V 50/60Hz.
<b>Temperature:</b>	Operating: 32° F to 104° F (0° C to 40° C). Storage: -4° F to 140° F (-20° C to 60° C).
<b>Humidity:</b>	Operating: 20% to 80% RH (Non-Condensing). Storage: 10% to 90% RH (Non-Condensing).
<b>Dimensions:</b>	Tablet: 279 (W) x 178 (H) x 22 (D) mm.
<b>Weight:</b>	2.20 lbs.

## Hisense

Also available

- High Performance Rugged POS Terminals.



YOUR DEALER IS:-

**elePOS**

**Tel: 0208 472 6661**

**Web: www.elepos.com**

**Hisense**

Distributed in the UK & NI by YCR Distribution Ltd. 01924 438238. Whilst every effort has been made to provide current photographs, descriptions and specifications the manufacturers reserve the right to change specifications, illustrations, model number and appearance of any item without prior notifications and therefore will not be held responsible for any variations.