

# **PAR//NER**

CARE . TRUST . RESPONSIBILITY

## **Thermal Printer RP-600** The most versatile Printer



The RP-600 is a fast thermal printer solution for retail and hospitality. With a paper width of 58 to 80 mm and a printing speed up to 230 mm/sec it is rather flexible.

The RP-600 is ENERGY STAR qualified and offers print options that reduce paper consumption up to 35%.

The quality of graphic printings is improved by gray scale printing. Furthermore the print direction is rotatable whereby the fonts can be printed in different directions (right and up) which makes the print design unique and helpful for the customer to read the receipt. All types of international characters are available, which can be enlarged 1-6 times horizontally and vertically.

Water mark prints can also be used optionally, making retail shops and supermarket printings individual and recognizable. Because of the wide range of interfaces and drivers quick and easy installation is guaranteed and simple integration to POS environments is provided.

### **Special features**

- Paper saving option
- Gray scale printing
- Rotatable print direction
- Integrated wall mounting (allows multiple placement options)
- Printing speed up to 230 mm/s (text & graphics)
- Autocutter (partial)
- Paper sensor (near/end)
- ENERGY STAR® qualified

### **Optional**

- Interfaces: Parallel, Serial, Ethernet, WLAN

## Thermal Printer RP-600

### Technical data

|                    |   |                           |            |
|--------------------|---|---------------------------|------------|
| Item               | RP-600  |                           |            |
| Printing Method    | Direct thermal  |                           |            |
| Printing Speed     | 230 mm/sec in text printing; 150 mm/sec in graphic printing   |                           |            |
| Dot Density        | 180 dpi   |                           |            |
| Dot Pitch          | 0.141 mm  |                           |            |
| Effective Printing | Width: 72 mm max.   |                           |            |
| Character per Line | Font A: (12 x 24)<br>42 columns (80mm) 30 columns (58mm)<br>Font B: (9 x 17) 56 columns<br>56 columns (80 mm) 40 columns (58 mm)  |                           |            |
| Paper              | Type:   | Thermal paper, black mark |            |
|                    | Width:  | 57.5~82.5 mm              |            |
|                    | Print width:  | 72 mm max.                |            |
|                    | Roll Ø:   | 83 mm                     |            |
|                    | Roll core inner Ø:  | 12.5 mm +/- 0.5 mm        |            |
| Sensor             | Paper end, paper near end, cover open, print head temperatur, printer voltage detection   |                           |            |
| I/O Interface      | Standard: USB 2.0 & Cash Drawer (2 Signals), support virtual COM port driver  |                           |            |
|                    | Optional interfaces: Serial, Parallel, Ethernet, WLAN   |                           |            |
| Power supply       | 100~240VAC, Input,DC+24V output   |                           |            |
| Dimension          | 143(W) x 190(D) x 143(H)  |                           |            |
| Weight             | 2.1 kg  |                           |            |
| Environment        | Operating   | Storage                   |            |
|                    | Temperature   | 5°C~45°C                  | -40°C~60°C |
|                    | Humidity  | 20%~90%                   | 20%~93%    |
| Auto Cutter Type   | Guillotine  |                           |            |
| Cutting Method     | Full cut, partial cut, tear-off   |                           |            |
| Reliability        | Printhead:  | 150Km                     |            |
|                    | Cutter:   | 1,500,000 cuts            |            |
|                    | MCBF:   | 60,000,000 lines          |            |
|                    | MTBF:   | 360,000 hours             |            |
| Driver             | Windows (XP, POSReady 2009, Server 2003/2008, Win 7, POSReady 7)<br>Linux (CUPS for Ubuntu, Fedora)<br>MAC (CUPS)<br>OPOS (Windows 32/64 bit)<br>JavaPOS (Windows, Linux) |                           |            |
| Color              | Black   |                           |            |



RP-600 is ENERGY STAR certified



Easy drop-in paper loading



Various I/O interfaces guarantee quick and easy installation



Adjustment for paper near end position (6 levels) and for 2" or 3" paper roll inside of RP-600

