

SAMSUNG

T H E R M A L R E C E I P T P R I N T E R



SRP-350
Thermal Receipt Printer

Best Thermal Receipt Printer SRP-350 completely satisfy you with versatile functions such as fast printing speed, compact size, easy paper supply D & P (Drop and Print) at any store environment.

Specially USB Interface help you connect the recent PC POS terminal. And If you want to change interface, you can set other interface easily without buying new printer (Modular I/F design).

SRP-350

Thermal Receipt Printer

• Dimension



• D & P (Drop and Print) Paper Supply



• Back Side



- Serial Interface
- Drawer Kick-out
- Power Jack

- Fastest Printing Speed (150mm / sec, 47.2 LPS)
- Multiple Interface (RS-232C, RS-485, USB, IEEE-1284) Modular Interface Card
- Saves Install Space (Compact Size, Wall-Mount)
- Easy-to-use
 - D & P (Drop and Print) paper supply
 - Simple to eliminate Paper Jam
 - Complete Compatibility

■ Specifications

		SRP-350
PRINT	Printing Method	Direct Thermal
	Printing Speed	132 mm / sec
	Dot Density	180 dpi (7 dot / mm)
	Printing Direction	Unidirectional with friction feed
	Character per Line	Font A : 42 Font B : 56
PAPER SPECIFICATION	Paper Type	Thermal Paper
	Paper width	79.5 ± 0.5 mm
	Paper Roll Diameter	Max. Ø 83.0 mm
PAPER SUPPLY METHOD		D & P (Drop and Print) Mechanism
RELIABILITY	MCBF	37,000,000 Lines
	TPH Life	1 x 10 ⁸ pulse, 100 km
CHARACTER SET		Alphanumeric Character : 95
		Extended Graphic : 128 x 7 page (1 space page)
		International character : 32
BARCODE		EAN-13, EAN-8, CODE 39, CODE 93, CODE 128, ITF, CODE BAR, UPC-A, UPC-E
EMULATION		TM-88 (II), TSP552 (II)
DRIVER		DOS, Windows 3.1 / 95 / 98 / NT
SENSOR		Near end sensor, Paper end sensor
DRAWER PORT		2 port
INTERFACE		RS-232C (Standard)
OPTION I / F CARD		RS-232C, RS-485, USB, IEEE-1284
POWER SUPPLY		AC 120V ~ 230V ± 10% (Adapter)
DIMENSION (W X L X H mm)		145 x 195 x 146
AUTO CUTTER	Type	Guillotine
	Life	500,000 cuts

■ Options

WM-350

Wall Mount Bracket



* Design and specifications are subject to change without notice.



HEAD OFFICE (SEOUL, KOREA)

6th Fl., Samsung Main Bldg. 250, 2-Ka
Taepyeong-Ro, Chung-Ku Seoul, Korea 100-742
TEL: +82 2 751 2785, 2790 FAX: +82 2 751 2680
Internet Homepage : <http://samsungelectronics.com>

Distributed by: